

# carrier.update

## Overview

This method allows you to update an existing carrier in Komet Sales.

## Request

<https://api.kometsales.com/api/carrier.update>

- **Method:** POST
- **Content-Type:** application/json

### Input Parameters:

- **authenticationToken** (required)(string:50): Komet Sales security token.
- **carrierId** (required)(integer:20): Komet Sales internal ID of the carrier that you want to update. You can obtain this value from the [carrier.list](#) API method.
- **name** (required)(string:200): name of the carrier.
- **code** (required)(string:10): code of the carrier.
- **active** (optional)(boolean:1): 1 if the carrier is active, 0 if the carrier is not active.
- **capacity** (optional)(integer:10): capacity of the carrier in cubes.

```
{
  "authenticationToken": "token_info_goes_here",
  "carrierId": 234234,
  "name": "Armellini",
  "code": "AR",
  "capacity": "200"
}
```

## Response

### Output:

- **status** (integer:1): transaction status. 1 for success or 0 for failure.
- **message** (string:500): description of the status of the transaction.
- **carrierId** (integer:20): carrier internal ID that was just updated.

```
{
  "status": "1",
  "message": "The carrier was successfully saved.",
  "carrierId": 234234
}
```

### Related Articles

- [Adding Carriers](#)
- [carrier.add](#)
- [carrier.list](#)
- [carrier.update](#)
- [Cut Off Time](#)
- [How to Edit an Invoice](#)